

## PERFORMANCE5™ BALEWRAP FILM 1.00 mil



### Product Description

Performance5™ is a high performance silage film that delivers high feed value efficiently and profitably. Quality and performance are consistent throughout. Ideal for wrapping big squares, round bales and for high-speed wrapping. Available in 20 and 30 inch widths.

Film Properties	Typical Value (English)	Tolerance	Test Method
Tensile Strength at Yield MD	1550 psi	± 15%	ASTM D882
Tensile Strength at Yield TD	1600 psi	± 15%	ASTM D882
Tensile Strength at Break MD	6700 psi	± 15%	ASTM D882
Tensile Strength at Break TD	4600 psi	± 15%	ASTM D882
Elongation at Break MD	600%	± 15%	ASTM D882
Elongation at Break TD	830%	± 15%	ASTM D882
Protrusion Puncture	12 lbs.	± 15%	ASTM D5748
Protrusion Puncture Energy	26.0 in-lb	± 15%	ASTM D5748
Elmendorf Tear Strength MD	140 g/mil	± 15%	ASTM 1922
Elmendorf Tear Strength TD	500 g/mil	± 15%	ASTM 1922
Cling - Outside to Inside @ 225%	min 200 g/in	± 15%	ASTM D5458

Dimensions	Value	Tolerance
Core ID	3.05 inches	± 0.05%
Film Thickness	25.4 micron	

**Manufactured with pride in Canada by  
Sigma Stretch Film of Canada**  
219 Jamieson Bone Rd Belleville Ontario K8N-5A5  
Phone: 866-848-4400 • 613-966-2781  
Email: stretch.info@sigmaplastics.com  
Visit our website at [www.sigmastretchfilm.com](http://www.sigmastretchfilm.com)  
©Copyright 2018 Sigma Stretch Film